

# Marine Transformer

Marine transformer is an isolation transformer which is used commonly in marine industries. Can be design with custom specification in term of inrush, efficiency, etc based on marine standard and certification.



## Specifications

### Standard Compliance

- ✓ IEC 60076
- ✓ EN 61558

### Primary/Secondary Voltage Range

- ✓ Up to 1000V

### Winding Material

- ✓ Aluminium Foil
- ✓ Copper Foil
- ✓ Enameled/Nomex insulation Aluminium Wire
- ✓ Enameled/Nomex insulation Copper Wire

### Silicon Steel

- ✓ Non Grained Oriented Silicon Steel (NGO)
- ✓ Grained Oriented Silicon Steel (GO)

### Varnish

- ✓ High grade polyester varnish

### Insulation Class

- ✓ Based on IEC 60085 Insulation Thermal Class
- ✓ Class Y (90°)
- ✓ Class A (105°)
- ✓ Class E (120°)
- ✓ Class B (130°)
- ✓ Class F (155°)
- ✓ Class H (180°)
- ✓ Class N (200°)

### Cooling

- ✓ Air Natural Cooling (AN)
- ✓ Air Force Cooling (AF)

### Ambient Temperature

- ✓ Maximum ambient temperature 40°C
- ✓ Up on customer request

### Metal Enclosure Protection Class

- ✓ Standard enclosure IP20
- ✓ Up to enclosure IP43

### Certifications

- ✓ CE
- ✓ BV
- ✓ ABS

### Capacity

- ✓ Up to 2000KVA



## Product Enquiry

### Contact:

Email : sales@tamura.com.my

Telephone : +6 03 5525 6000

Fax No : +6 03 5510 1013

[Send Enquiry](#)

## Catalog

[Download PDF](#)



## CONTACT US

Tamura Electronics (M) Sdn. Bhd. (17297-M),  
Lot No.2, Jalan Halba 16/16, Seksyen 16,  
40200 Shah Alam,  
Selangor, Malaysia.

☎ Telephone : 603-5525 6000  
📠 Fax : 603-5510 1013  
✉ E-Mail : sales@tamura.com.my