

# Open Vee Transformer

Open Vee transformer is an isolation transformer which is most common type of transformer used to supply a single phase system from a 3 phase supply is the Open Delta Transformer.



## Specifications

### Standard Compliance

- ✓ IEC 60076
- ✓ EN 61558

### Primary/Secondary Voltage Range

- ✓ Up to 1000V

### Winding Material

- ✓ Aluminium Foil
- ✓ Copper Foil
- ✓ Enameled/Nomex insulation Aluminium Wire
- ✓ Enameled/Nomex insulation Copper Wire

### Silicon Steel

- ✓ Non Grained Oriented Silicon Steel (NGO)
- ✓ Grained Oriented Silicon Steel (GO)

### Varnish

- ✓ High grade polyester varnish

### Insulation Class

- ✓ Based on IEC 60085 Insulation Thermal Class
- ✓ Class Y (90°)
- ✓ Class A (105°)
- ✓ Class E (120°)
- ✓ Class B (130°)
- ✓ Class F (155°)
- ✓ Class H (180°)
- ✓ Class N (200°)

### Cooling

- ✓ Air Natural Cooling (AN)
- ✓ Air Force Cooling (AF)

### Ambient Temperature

- ✓ Maximum ambient temperature 40°C
- ✓ Up on customer request

### Metal Enclosure Protection Class

- ✓ Standard enclosure IP20
- ✓ Up to enclosure IP43

### Certifications

- ✓ CE

### Capacity

- ✓ Up to 2000KVA



## Product Enquiry

### Contact:

Email : [sales@tamura.com.my](mailto:sales@tamura.com.my)

Telephone : +6 03 5525 6000

Fax No : +6 03 5510 1013

[Send Enquiry](#)

## Catalog

[Download PDF](#)



## CONTACT US

Tamura Electronics (M) Sdn. Bhd. (17297-M),  
 Lot No.2, Jalan Halba 16/16, Seksyen 16,  
 40200 Shah Alam,  
 Selangor, Malaysia.

☎ Telephone : 603-5525 6000

📠 Fax : 603-5510 1013

✉ E-Mail : [sales@tamura.com.my](mailto:sales@tamura.com.my)